

AVK 2,5 Blue

Klemsan

304121

2,5mm² Screw type,single deck feed through terminal block

Category: Screw Type Terminal Blocks

Type: Feed Through Terminals

Group: Terminal Blocks

Commercial Information

Package Unit	100 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0,0064

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Blue
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III

Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120
Continuous Operating Temperature min.	-55
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8
Nominal Current	24
Nominal Voltage	750
Maximum Load Current	32
CONNECTION DATA	
Connection Type	Screw Connection
Single-core min. conductor cross-section	0,2
Single-core max. conductor cross-section	4
Conductor cross-section AWG/kcmil min.	24
Conductor cross-section AWG/kcmil min.	-
Conductor cross-section AWG/kcmil max.	12
Multi-core min. conductor cross-section	0,2
Multi-core max. conductor cross-section	4
Multi-core min. conductor cross-section with ferrule	0,25
Multi-core max. conductor cross-section with ferrule	2,5
2 conductors of the same cross-section, multi-	0,5

core, twin ferrule with plastic sleeve, min.	
2 conductors of the same cross-section, multi-core, twin ferrule with plastic sleeve, max.	1,5
Min. Stripping Length	9
Max. Stripping Length	10
Internal cylindrical indicator	A3
Tightening torque, min	0,4
Tightening torque, max.	0,6
DIMENSIONS	
Width	5
Length	44,2
Height MR 35x7.5	44,4
Height MR 35x15	51,9